Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: RBC2A

UPS Replacement Battery Cartridge for select APC UPS

Highlights

- Up to 30% longer runtime than basic replacements
- OEM certified premium batteries
- Rugged, leakproof construction
- Maintenance-free
- Wide operating temperature range

Description

Tripp Lite's premium UPS replacement battery cartridges breathe new life into UPS systems suffering from expired or weak internal batteries. Each replacement battery set is carefully configured to meet or exceed all of the original manufacturer specifications and ships pre-assembled and ready for installation into your UPS system. Reusable packaging holds expired batteries for recycling center delivery. Compatible with select UPS systems from APC and other major brands. See Tripp Lite's UPS replacement battery page to confirm compatibility and quantity required. Includes 18 month warranty.

Applications

- Extends the operating life of older UPS systems
- Restores or enhances runtimes of UPS systems exhibiting reduced power failure runtime

Package Includes

- UPS battery replacement cartridge
- Instruction manual with installation, recycling and warranty information

Features

- Restores your UPS to its original runtime specifications
- Comes pre-assembled and ready for installation into your UPS system
- Reusable packaging holds expired batteries for recycling center delivery
- Compatible with many brands and models, including APC models BK200, BK250B, BK280B, BP280, BP280PNP, BP280C, BP280S, BK300, BK350, BK400, BK400B, BP420, BP420C, BP420PNP, BP420S, BK500M, PCPER, PCPRO, SUVS420, SU420NET, BP350UC, BP500CLR, BP500UC
- Includes 18 month warranty

Specifications

BATTERY	
Typical battery lifespan	3 - 5 years, depending on host UPS operating conditions
PHYSICAL	

Shipping weight (lbs)	7
Shipping weight (kg)	3.2
Shipping Dimensions (HWD/in)	6 x 7.5 x 12
Shipping Dimensions (HWD/cm)	15.2 x 19.1 x 30.5
Unit weight (lbs)	5.5
Unit weight (kg)	2.5
Unit Dimensions (HWD/in)	3.6875 x 2.5 x 5.875
Unit Dimensions (HWD/cm)	9.4 x 6.4 x 14.9
ENVIRONMENTAL	
Relative Humidity	0 - 95% non-condensing
Operating Elevation (ft)	0 - 10,000
Storage Elevation (ft)	0 - 50,000

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=2534.

©2009 Tripp Lite. All Rights Reserved.